



## WAR H10 Series Card Readers

The WatchNET H10 Series HID Compatible Card Readers are unique combination of style and reliability making it an ideal choice for entry level access control, time attendance or for large and complex installations. The unit resists the elements such as glue, oil, rain, ice, snow making it ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control. Blue backlit LED assists operation in low or no light conditions and along with a built in internal sounder, this reader provides superior accessibility. This superior quality Proximity reader is rugged, weather-resistant, and attractive in design with also has an exceptionally long life due to no moving parts.

- HID Compatible Card Readers
- Keypad Readers with Display
- Vandal Resistant Readers
- Clamshell Cards
- Printable Cards
- Key Fobs

Model	WAR-H10-STB	WAR-H10-COM	WAR-H10-DKP	WAR-H10-VKR	WAR-H10-VKC
					
Description					
Range in cm	14	10	10	10	10
Output	26/34 bit	26/34 bit	26/34 bit	26/34 bit	26/34 bit
Indicators	Blue/Green	Blue/Green	Blue/Green	Blue/Green	Blue/Green
Size in mm	86 x 86 x 15	43 x 86 x 16	126 x 95 x 25	120 x 76 x 21	153 x 46 x 18
Frequency	125 KHz	125 KHz	125 KHz	125 KHz	125 KHz
Voltage	6 - 15V DC	6 - 15V DC	6 - 15V DC	6 - 15V DC	6 - 15V DC
Operating Current	≤100mA	≤100mA	≤100mA	≤100mA	≤100mA
Standby Current:	≤50mA	≤50mA	≤50mA	≤50mA	≤50mA
Working Temperature	-30°C to 65°C (-22°F to 150°F)	-30°C to 65°C (-22°F to 150°F)	-30°C to 65°C (-22°F to 150°F)	-30°C to 65°C (-22°F to 150°F)	-30°C to 65°C (-22°F to 150°F)
Operating Humidity	0 to 95%	0 to 95%	0 to 95%	0 to 95%	0 to 95%
LED Control Input	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O
Buzzer Control Input	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O	Dry Contact, N/O
Weight	300 g (0.66 lbs.)	100 g (0.22 lbs.)	200 g (0.44 lbs.)	500 g (1.10lb)	500 g (1.10lb)

All product specifications on this brochure are subject to change without notice.

**CANADA:**  
351 Ferrier Street, Unit 5  
Markham, Ontario  
L3R 5Z2, Canada  
Tel: 416-410-6865  
Fax: 1-866-331-3341  
Toll Free: 1-866-843-6865

**USA:**  
700 Ensminger Rd. Site 104  
Tonawanda, NY  
14150 USA  
Toll Free: 1-866-843-6865  
Local: 1-717-687-8736  
Fax: 1-866-331-3341

[www.watchnetaccess.com](http://www.watchnetaccess.com)  
[info@watchnetaccess.com](mailto:info@watchnetaccess.com)

**UAE:**  
P.O.Box # 8425  
Dubai, UAE  
Tel: + 971 4 3963067  
Fax: + 971 4 3963067  
Mobile: + 971 50 5869290

**INDIA:**  
E-98, Ground Floor  
Lajpat Nagar-I  
New Delhi-110024  
Tel: +91 11 29824005  
Fax: +91 11 29824006