



WORK SAFER WHEREVER THE MISSION TAKES YOU

APX™ 1500 PROJECT 25 MOBILE RADIO

Whether a marathon race is passing through the streets of downtown or a water main breaks in the city's largest pipeline, you need the ability to interoperate seamlessly and securely with other agencies and responders. You need to instantly connect and be informed to make better decisions to keep your responders and the community safe. While the advanced technology of APX radios expertly equips you for your day to day operations and the unexpected, your organization may be challenged to improve operating expenses.

The APX 1500 P25 mobile radio is equipped with all the features you need at a price you can afford. It delivers all the benefits of TDMA technology in the most compact P25 capable mobile in the industry. The APX 1500 brings together powerful technology in an easy-to-use radio that's easy on your budget. It seamlessly unifies public works, utility, rural public safety and transportation users to first responders so they can interoperate effectively in the moments that matter.

BE UP TO THE MINUTE INFORMED

Keeping your crew safe is your number one priority. Like all our APX P25 radios trusted by responders worldwide, the APX 1500 mobile redefines safety. Your crews can count on quick, seamless interoperability and extended range wherever the mission may take them. You can depend on ADP software encryption for secure, tamperproof voice and data communications every time they connect.

The O2 Control Head with color display is easy to read and operate in all lighting conditions, from bright sunlight to dark streets. The intelligent lighting on the O2 Control Head notifies your workers when a call is received, an emergency arises, or when they are out of range. Plus, an enlarged multifunction knob makes it easy to use talk-group and volume settings when they're wearing gloves.

SIZED RIGHT FOR YOUR BUDGET

The APX 1500 gives you the ruggedibility and reliability you need at an affordable price. Since the APX 1500 is P25 Phase 2 capable for twice the voice capacity, you can add more users without adding more frequencies or infrastructure. Count on APX quality for years to come. The APX 1500 can withstand wet, dusty and hazardous conditions.

PRODUCT DATA SHEET
APX™ 1500 MOBILE RADIO



APX 1500 SPECIFICATIONS

FEATURES AND BENEFITS:

Available in 700/800 MHz, VHF, UHF R1 and UHF R2 frequency bands

Channels: Standard 512

Trunking Standards supported:

- Clear or digital private Trunked Operation

Analog MDC-1200 and Digital APC0 P25 Conventional System Configurations

Narrow and wide bandwidth digital receiver (6.25kHz/12.5kHz/20kHz/25 kHz)

Embedded digital signaling (ASTRO and ASTRO 25)

Intelligent lighting

Radio profiles

Unified Call List

Meets applicable MIL-STD 810C, D, E, F, G

Ships standard IP56

Utilizes Windows XP, Vista and Windows 7 and 8 Customer Programming Software (CPS)*

- Supports USB Communications
- Built in FLASHport™ support

Uses standard Dash mounted APX accessories

Software Key

ASTRO 25 Integrated Voice and Data

ADP Privacy

OPTIONAL FEATURES:

GPS Outdoor Location Tracking

Programming over Project 25 (POP25)

Text Messaging

12 character RF ID asset tracking

* CPS version R12.00.00 and greater ordered after June 2014 will only support Windows 7 and 8

APX 1500 CONTROL HEAD PORTFOLIO



O2 RUGGED CONTROL HEAD

- Large color display with intelligent lighting
- 3 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Built in 7.5 watt speaker
- Multifunction volume/channel knob
- Night/day mode button

PRODUCT DATA SHEET
APX™ 1500 MOBILE RADIO

| TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS | | | | | | | | | | |
|---|-------------------------------------|------------------|-------------------------------------|------------------|-------------------|------------------|--------------------|------------------|--------------------|------------------|
| | 700 MHz | | 800 MHz | | VHF | | UHF Range 1 | | UHF Range 2 | |
| Frequency Range/Bandsplits | 764-776 MHz 794-806 MHz | | 806-824 MHz 851-870 MHz | | 136-174 MHz | | 380-470 MHz | | 450-520 MHz | |
| Channel Spacing | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | |
| Maximum Frequency Separation | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | |
| Rated RF Output Power Adj* | 3-30 Watts (2-3 Watts Itinerant) | | 3-35 Watts | | 1-50 Watts | | 1-40 Watts | | 1-45 Watts | |
| Frequency Stability* (-30°C to +60°C; +25°C Ref.) | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | |
| Modulation Limiting* | ±5 kHz / ±2.5 kHz | | ±5 kHz/±4 kHz (NPSPEC) /±2.5 kHz | | ±5 kHz / ±2.5 kHz | | ±5 kHz / ±2.5 kHz | | ±5 kHz / ±2.5 kHz | |
| Modulation Fidelity (C4FM) 12.5kHz Digital Channel | 1.5% | | 1.5% | | 2.5% | | 1.1% | | 1.1% | |
| Emissions* | Conducted+ | Radiated+ | Conducted+ | Radiated+ | Conducted+ | Radiated+ | Conducted+ | Radiated+ | Conducted+ | Radiated+ |
| | -75/-85 dBc | -20/-40 dBm | -75 dBc | -20 dBm | -85 dBc | -20 dBm | -85 dBc | -20 dBm | -85 dBc | -20 dBm |
| Audio Response* | +1, -3 dB (EIA) | | +1, -3 dB (EIA) | | +1, -3 dB (EIA) | | +1, -3 dB (EIA) | | +1, -3 dB (EIA) | |
| FM Hum & Noise | 25 & 20 kHz 12.5 kHz | -50 dB -48 dB | -50 dB -48 dB | -50 dB -48 dB | -52 dB -51 dB | -51 dB -48 dB | -51 dB -48 dB | -51 dB -48 dB | -51 dB -48 dB | -51 dB -48 dB |
| Audio Distortion* | 25 & 20 kHz 12.5 kHz | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% | 0.50% 0.50% |

| RECEIVER – TYPICAL PERFORMANCE SPECIFICATIONS | | | | | | | | | | |
|--|------------------------------|---------------------|---------------------|---------------------|-------------------------|----------------------|---------------------|----------------------|---------------------|----------------------|
| | 700 MHz | | 800 MHz | | VHF | | UHF Range 1 | | UHF Range 2 | |
| Frequency Range/Bandsplits | 764-776 MHz | | 851-870 MHz | | 136-174 MHz | | 380-470 MHz | | 450-520 MHz | |
| Channel Spacing | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | | 25/20/12.5 kHz | |
| Maximum Frequency Separation | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | | Full Bandsplit | |
| Audio Output Power at 3% distortion* | 7.5 W or 15 W ++ | | 7.5 W or 15 W ++ | | 7.5 W or 15 W ++ | | 7.5 W or 15 W ++ | | 7.5 W or 15 W ++ | |
| Frequency Stability* (-30°C to +60°C; +25°C Ref.) | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | | ±0.8 PPM | |
| Analog Sensitivity* | 12 dB SINAD | -120 dBm | -120 dBm | -120 dBm | Pre-Amp -123 dBm | Standard -119 dBm | Pre-Amp -123 dBm | Standard -119 dBm | Pre-Amp -123 dBm | Standard -119 dBm |
| Digital Sensitivity | 5% BER | -121 dBm | -121 dBm | -121 dBm | -123 dBm | -119 dBm | -123 dBm | -119 dBm | -123 dBm | -119 dBm |
| Intermodulation Rejection | 25 kHz 12.5 kHz | 82 dB 82 dB | 82 dB 82 dB | 82 dB 82 dB | 84 dB 85 dB | 86 dB 86 dB | 82 dB 83 dB | 86 dB 85 dB | 82 dB 83 dB | 86 dB 85 dB |
| Spurious Rejection | 91 dB | | 91 dB | | 95 dB | | 91 dB | | 91 dB | |
| Audio Distortion at rated* | 2% | | 2% | | 2% | | 2% | | 2% | |
| Selectivity* | 25 kHz 12.5 kHz 30 kHz | 85 dB 75 dB — | 85 dB 75 dB — | 85 dB 75 dB — | 89 dB 77 dB 90 dB | 83 dB 72 dB — | 83 dB 72 dB — | 83 dB 72 dB — | 83 dB 72 dB — | 83 dB 72 dB — |

| DIMENSIONS | | |
|--|-----------------|--------------------|
| | Inches | Millimeters |
| Mid Power Radio Transceiver | 2 x 7 x 6.4 | 50.8 x 178 x 163 |
| O2 Control Head | 2.7 x 8.1 x 2.1 | 69 x 207 x 53 |
| Mid Power Radio Transceiver and O2 Control Head - Dash Mount | 2.7 x 8.1 x 8.8 | 69 x 207 x 223 |
| Mid Power Radio Transceiver and O2 Control Head Weight | 5.28 lbs | 2.45 kg |

| RADIO MODELS | |
|---------------------------|--------------|
| 700/800 (763-870 MHz) | M36UR9PW1AN |
| VHF (136-174 MHz) | M36KSS9PW1AN |
| UHF Range 1 (380-470 MHz) | M36QSS9PW1AN |
| UHF Range 2 (450-520 MHz) | M36SSS9PW1AN |

| SIGNALING (ASTRO MODE) | |
|---|---|
| Signaling Rate | 9.6 kbps |
| Digital ID Capacity | 10,000,000 Conventional / 48,000 Trunking |
| Digital Network Access Codes | 4,096 network site addresses |
| ASTRO® Digital User Group Addresses | 4,096 network site addresses |
| Project 25 – CAI Digital User Group Addresses | 65,000 Conventional / 4,094 Trunking |
| Error Correction Techniques | Golay, BCH, Reed-Solomon codes |
| Data Access Control | Slotted CSMA: Utilizes infrastructure-sourced data status bits embedded in both voice and data transmissions. |

PRODUCT DATA SHEET
APX™ 1500 MOBILE RADIO

POWER AND BATTERY DRAIN

| | | | | | |
|---|--|------------|--------------------------|-----------------|------------|
| Model Type | 136-174 MHz, 380-470 MHz, 450-520 MHz, 764-870 MHz | | | | |
| Minimum RF Power Output | 2***-25 Watts (764-776 MHz), 2***-25 Watts (794-806 MHz), 2***-25 Watts (806-824 MHz), 2***-25 Watts (851-870 MHz), 1-25 Watts (136-174 MHz), 1-25 Watts (380-470 MHz), 1-25 Watts (450-520 MHz) | | | | |
| Operation | 13.8V DC ±20% Negative Ground | | | | |
| Standby at 13.8V | 0.85A (764-870 MHz), 0.85A (136-174 MHz), 0.85A (380-470 MHz), 0.85A (450-520 MHz) | | | | |
| Receive Current at Rated Audio at 13.8V | 3.2A (764-870 MHz), 3.2A (136-174 MHz), 3.2A (380-470 MHz), 3.2A (450-520 MHz) | | | | |
| Transmit Current (A) at Rated Power | 136-174 MHz (1-25 Watt) | 9.5A (25W) | 764-870 MHz (10-35 Watt) | (2***-25 Watts) | 9.5A (25W) |
| | 380-470 MHz (1-25 Watt) | 9.5A (25W) | | | |
| | 450-520 MHz (1-25 Watt) | 9.5A (25W) | | | |

MOBILE MILITARY STANDARDS 810 C, D, E, F, G

| | MIL-STD 810C | | MIL-STD 810D | | MIL-STD 810E | | MIL-STD 810F | | MIL-STD 810G | |
|----------------------------|--------------|-----------------|--------------|------------|--------------|------------|--------------|------------|--------------|---------------|
| | Method | Proc./Cat. | Method | Proc./Cat. | Method | Proc./Cat. | Method | Proc./Cat. | Method | Proc./Cat. |
| Low Pressure | 500.1 | I | 500.2 | II | 500.3 | II | 500.4 | II | 500.5 | II |
| High Temperature Storage | 501.1 | I | 501.2 | I/A1 | 501.3 | I/A1 | 501.4 | I/Hot | 501.5 | I/A1 |
| High Temperature Operation | 501.1 | II | 501.2 | II/A1 | 501.3 | II/A1 | 501.4 | II/Hot | 501.5 | II |
| Low Temperature Storage | 502.1 | I | 502.2 | I/C3 | 502.3 | I/C3 | 502.4 | I/C3 | 502.5 | I/C3 |
| Low Temperature Operation | 502.1 | I | 502.2 | II/C1 | 502.3 | II/C1 | 502.4 | II/C1 | 502.5 | II |
| Temperature Shock | 503.1 | - | 503.2 | I/A1-C3 | 503.3 | I/A1-C3 | 503.4 | I/Hot-C3 | 503.5 | I/C |
| Solar Radiation | 505.1 | II | 505.2 | I | 505.3 | I | 505.4 | I | 505.5 | I/A1 |
| Rain Blowing | 506.1 | I | 506.2 | I | 506.3 | I | 506.4 | I | 506.5 | I |
| Rain Steady | 506.1 | II | 506.2 | II | 506.3 | II | 506.4 | III | 506.5 | III |
| Humidity | 507.1 | II | 507.2 | II | 507.3 | II | 507.4 | - | 507.5 | II-Aggravated |
| Salt Fog | 509.1 | - | 509.2 | - | 509.3 | - | 509.4 | - | 509.5 | 1 Proc |
| Blowing Dust | 510.1 | I | 510.2 | I | 510.3 | I | 510.4 | I | 510.5 | I |
| Blowing Sand | | - | 510.2 | II | 510.3 | II | 510.4 | II | 510.5 | II |
| Vibration Min. Integrity | 514.2 | VIII/F, Curve-W | 514.3 | I/10 | 514.4 | I/10 | 514.5 | I/24 | 514.6 | I-Cat.24 |
| Vibration Loose Cargo | 514.2 | XI | 514.3 | II/3 | 514.4 | II/3 | 514.5 | II/5 | 514.6 | - |
| Shock Functional | 516.2 | I | 516.3 | I | 516.4 | I | 516.5 | I | 516.6 | I, V, VI |

ENCRYPTION

| | |
|---------------------------------|--|
| Supported Encryption Algorithms | ADP SW |
| Encryption Type | Digital |
| Key Storage | Tamper protected volatile or non-volatile memory |
| Key Erasure | Keyboard command |

* Measured in the analog mode per TIA/EIA 603 under nominal conditions
 ** Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)
 + Specs includes performance for the non-GNSS/GNSS bands
 ++ Output power in to 8 and 3.2 Ohm external speakers respectively

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

Version 2, Dec 14

ENVIRONMENTAL SPECIFICATIONS

| | |
|--------------------------|---------------|
| Operating Temperature | -30°C / +60°C |
| Storage Temperature | -40°C / +85°C |
| Humidity | Per MIL-STD |
| ESD | IEC 801-2 KV |
| Water and Dust Intrusion | IP56, MIL-STD |

TRANSMITTER CERTIFICATION

| | |
|--|-------------|
| 700/800 (764-775, 793-805, 806-824, 851-869 MHz) | AZ492FT7055 |
| VHF (136-174 MHz) | AZ492FT4916 |
| UHF R1 (380-470 MHz) | AZ492FT3826 |
| UHF R2 (450-520 MHz) | AZ492FT4915 |

FCC EMISSIONS DESIGNATORS

| | |
|---------------------------|--|
| FCC Emissions Designators | 8K10F1D, 8K10F1E, 8K10F1W, 11K0F3E, 16K0F3E, 20K0F1E |
|---------------------------|--|

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. www.motorolasolutions.com

MOTOROLA, MOTOROLA SOLUTIONS, and the stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © Motorola Solutions, Inc. 2014 R3-1-5000A

